



Tel: 08.3842.5266 – Fax: 08.3842.5266

Email: vietscreentienphat@gmail.com

Địa chỉ: 264 Lê Trọng Tấn, P. Tây Thạnh, Q. Tân Phú, TP. HCM

Model		BFR-500	BFR-800	BFR-1000	BFR-1250	Remark
Belt Width (mm)		500	800	1000	1250	
Treating Capacity (m ³ /hr)		1.0 ~ 2.0	2.0 ~ 4.0	4.0 ~ 6.0	6.0 ~ 8.0	(depends on the slurry feature)
Inlet Consistency (S.S 1.5~2.5%)						
D.S (kg/hr)		20 ~ 40	35 ~ 70	50 ~ 90	70 ~ 100	(depends on the slurry feature)
Water Contents Rate (%)		66 ~ 85	66 ~ 85	66 ~ 85	66 ~ 85	(depends on the slurry feature)
Power Consumption (HP)	Driving Motor (Speed Variable)	1/2	1/2	1/2	1/2	
	Disposal Agitator Motor	1/4	1/4	1/4	1/2	
	Drum Thickener	1/4	1/4	1/4	1/4	
External	L	2150	2250	2400	2400	Pls ask for the actual Dimension before ordering
Dimensions	W	1050	1300	1550	1800	
(Reference)(mm)	H	2400	2400	2500	2600	
Base Dimension L1 x W1 (mm)		1460 x 854	1460 x 1104	1460 x 1354	1460 x 1604	
Reference Weight (kgs)		660	800	960	1220	

Model		BFR-1500	BFR-2000	BFR-2500	Remark
Belt Width (mm)		1500	2000	2500	
Treating Capacity (m ³ /hr) Inlet Consistency (S.S 1.5~2.5%)		8.0 ~ 10.0	15.0 ~ 20.0	20.0 ~ 25.0	(depends on the slurry feature)
D.S (kg/hr)		80 ~ 160	140 ~ 200	180~ 250	(depends on the slurry feature)
Water Contents Rate (%)		66 ~ 85	66 ~ 85	66 ~ 85	(depends on the slurry feature)
Power Consumption (HP)	Driving Motor (Speed Variable)	1	2	2	
	Disposal Agitator Motor	1/2	1	1	
	Drum Thickener	1/2	1/2	3/4	
External	L	2750	2860	3000	Pls ask for the actual Dimension before ordering
Dimensions	W	2050	2130	2630	
(Reference)(mm)	H	2700	2750	2650	
Base Dimension L1 x W1 (mm)		1460 x 1854	2110 x 1860	2110 x 2400	
Reference Weight (kgs)		1490	1800	2200	